05.40.00 (Cold-Formed Metal Framing)



# 3" x 3" SwiftClip™ LA-Series™ (LA543)

### 54mils (16ga) 3-1/4" Long Support Clip

SwiftClip LA-Series support clips are used in multiple construction projects, specifically in conjunction with structural studs and track. The L-shaped clips fit between the stud flanges, so that shorter length clips do not need to be ordered. These labor time-savers include prepunched holes for quicker screw attachments, and are punched to accommodate for CRC lateral bracing connections.

For allowable loads for multiple connection options, reference the Clip & Connector Catalog or www.clarkdietrich.com/SwiftClip for more information.

# **Product Data & Ordering Information:**

Material:	Structural Grade 50 Type H (ST50H), 50ksi (340 MPa)
Coating:	G90 (Z275) hot-dipped galvanized coating
Thickness:	54mils (16ga) 0.0566" Design thickness 0.0538" Minimum thickness
Dimensions:	3" x 3" x 3-1/4" (76.2mm x 76.2mm x 82.6mm)
Packaging:	100 pieces per bucket
Product Weight:	0.30 lb / piece

# **Code Approvals & Performance Standards**


- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- ASTM A1003 Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for Cold-Formed Framing Members
- SDS For ASTM A1003 Steel Framing Products For Interior Framing, Exterior Framing and Clips/Accessories

#### **Alternative Products:**


- FastBridge™ Clip
- EasyClip™ Support Clips

**Sustainability Credits** For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.


- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) Sourcing of Raw Materials (up to 2 points) Material Ingredients (1 point) Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) Sourcing of Raw Materials (1 point) Material Ingredients (1 point) Construction and Demolition Waste Management (up to 2 points) Innovation Credit (up to 2 points).




- Lengths Available: 3-1/4", 5-1/2", 7-1/4"
- Available in 16, 14 & 12 gauge
- Pre-punched for faster and more accurate fastener attachment



Joist-to-Joist Connections



 ${\sf Head\text{-}to\text{-}Jamb\,Connections}$ 



Sill-to-Jamb Connections