

2x6 FR Blocking

Precut fire-retardant treated wood blocking

Fire-retardant treated wood blocking for nonstructural steel framing with dado groove to latch on to flange and span between wall partitions to provide attachment surface for wall mounted fixtures.

Product Data & Ordering Information:

Product Code:	FRB26-16 (16" o.c. System)
Material:	Southern Yellow Pine (SYP) treated with D-Blaze® Fire-Retardant treatment
Dimensions:	1-1/2" x 5-1/2" x 15-3/4"
Packaging:	288 pieces per skid
Product weight:	2.35 lbs/piece

Features:

- D-Blaze® Fire-Retardant Treatment
- Dado groove provides secure and flush mounting surface.
- Pre-cut for "o.c. spacing
- Provides reinforcement to the structural integrity of the walls for stability of wall-mounted fixtures.

D-Blaze® FRT Wood Code Approvals:

D-Blaze
ASTM E84, ASTM D3201, ASTM D5516, ASTM D5664
Underwriters Laboratories Classified
UL GreenGuard Gold Certificate - UL 2818
California Department of Forestry and Fire Protection CSFM BML Listings for D-Blaze Lumber
National Fire protection Association (NFPA 255)
AWPA Standardized (Ps50, U1, UCFA) Interior Type A High-Temperature (HT) FRTW
City of Los Angeles Research Report: RR24502 in accordance with ICC-ES 2645
NY City Building Code (MEA Numbers 406-87 & 407-87)
National Build Code of Canada
UL Class A (Class 1) w/ FR-S Rating CAN/ULC S102 & S102.2
Class A FRT lumber
50 Year Warranty

- D-Blaze® is a registered trademark of Viance, LLC.

