

## 2x6 FR Blocking

### Precut fire-retardant treated wood blocking

Fire-retardant treated wood blocking for nonstructural steel framing with dado groove to latch on to flange and span between wall partitions to provide attachment surface for wall mounted fixtures.

### Product Data & Ordering Information:

<b>Product Code:</b>	FRB26-16 (16" o.c. System)
<b>Material:</b>	Southern Yellow Pine (SYP) treated with D-Blaze® Fire-Retardant treatment
<b>Dimensions:</b>	1-1/2" x 5-1/2" x 15-3/4"
<b>Packaging:</b>	288 pieces per skid
<b>Product weight:</b>	2.35 lbs/piece

#### Features:

- D-Blaze® Fire-Retardant Treatment
- Dado groove provides secure and flush mounting surface.
- Pre-cut for "o.c. spacing
- Provides reinforcement to the structural integrity of the walls for stability of wall-mounted fixtures.

### D-Blaze® FRT Wood Code Approvals:

<b>D-Blaze</b>
ASTM E84, ASTM D3201, ASTM D5516, ASTM D5664
Underwriters Laboratories Classified
UL GreenGuard Gold Certificate - UL 2818
California Department of Forestry and Fire Protection CSFM BML Listings for D-Blaze Lumber
National Fire protection Association (NFPA 255)
AWPA Standardized (Ps50, U1, UCFA) Interior Type A High-Temperature (HT) FRTW
City of Los Angeles Research Report: RR24502 in accordance with ICC-ES 2645
NY City Building Code (MEA Numbers 406-87 & 407-87)
National Build Code of Canada
UL Class A (Class 1) w/ FR-S Rating CAN/ULC S102 & S102.2
Class A FRT lumber
50 Year Warranty

- D-Blaze® is a registered trademark of Viance, LLC.

