

## #2A Expanded Corner Bead (CBXX)

### Rigid, expanded flange corner bead for exterior corners

A more rigid expanded corner bead for reinforcing plaster/stucco corners when used with masonry and fire proofing beads and columns. The #2A Corner Bead provides extra strength and rigidity by incorporating a wider 3-1/4" flange with an added stiffener ridge. The Double-X is an ideal choice for corners in high-traffic areas.

Strong and economical with multiple general use purposes, the wider, expanded-wing flanges are flexible and can compensate for most irregular surfaces, providing straight corners and even grounds with extra strength. Used to reinforce Portland cement stucco at external corners.

Galvanized steel products should not be used with Portland cement stucco containing calcium chloride additives or magnesium oxychloride cement stucco. The selection of the appropriate type of material for accessories shall be determined by the surrounding climatic and environmental conditions such as high humidity, salt air, and industrial pollution. The #2A Corner Bead is available in Zinc for approved corrosion resistance.

### Product Data & Ordering Information:

**Materials:** 26 Gauge, G-60 Hot-Dipped Galvanized Steel

**Dimensions:** 3-1/4" Full Wing Flange available in 10' lengths

| Length | Pcs./Ctn. | Ft./Ctn. | Ctn./Skid | Wt./Ctn. |
|--------|-----------|----------|-----------|----------|
| 10'    | 30        | 300'     | 20        | 66 lbs.  |

### Code Approvals & Performance Standards

- [ASTM A653](#) Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [SDS For ASTM A653 Steel Finishing Products](#) For Interior Finishing and Exterior Finishing

### Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather and surface contamination conforming to ASTM C1063.

### Limitations:

Galvanized steel products should not be used with magnesium oxychloride cement stucco or Portland cement stucco containing calcium chloride additives. The selection of the appropriate type of material for accessories shall be determined by the surrounding climatic and environmental conditions such as salt air, industrial pollution and high humidity.

**Sustainability Credits** For more details and LEED letters contact Technical Services at 888-437-3244 or visit [clarkdietrich.com/LEED](http://clarkdietrich.com/LEED).

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

