

#36 Sill Screed (SI36)

Exterior foundation sill screed

A variation of the #7 style screed which allows trowel access underneath the screed to clean excess stucco material. No visible metal is seen below the stucco line.

Installed at the juncture of the sill and exterior concrete foundation, or in similar areas, to allow trapped moisture to drain to the exterior of the building. Provides straight edge stops for applied plaster stucco and E.I.F.S. (Exterior Insulation Finishing Systems) with exacting grounds, as well as impact and splash protection at the bottom edge. Additionally, the #36 Sill Screed is ideal for wall to roof transitions.

The #36 style screed is manufactured in compliance with ASTM standards and has the minimum requirement of 26-gauge, G60 galvanized steel, and a 3-1/2" solid nailing flange.

Product Data & Ordering Information:

Material: 26 Gauge, G-60 Hot-Dipped Galvanized Steel

Dimensions: 3-1/2" Flange x 7/8" ground x 10' lengths

Ground	Flange	Length	Pcs./Bdl.	Pcs./Pallet	Wt./Pallet
7/8"	3-1/2"	10'	10	1000	2683

Also available without holes in the nose/ground.

Code Approvals & Performance Standards

- [ASTM A653](#) Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1780](#) Standard Practice for Installation Methods for Cement-based Adhered Masonry Veneer
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [SDS For ASTM A653 Steel Finishing Products](#) For Interior Finishing and Exterior Finishing

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather and surface contamination conforming to ASTM C1063.

Limitations:

Galvanized steel products should not be used with magnesium oxychloride cement stucco or Portland cement stucco containing calcium chloride additives. The selection of the appropriate type of material for accessories shall be determined by the surrounding climatic and environmental conditions such as salt air, industrial pollution and high humidity.

Related Accessories:

- #7 7/8" Foundation Sill Screed
- #7 1-3/8" Foundation Sill Screed

