

Striplath

Reinforcement for corners, windows, doors and openings

Striplath is a flat, expanded metal strip used as plaster reinforcement over joints of solid bases and where dissimilar bases join. It is flexible for use over irregular surfaces.

Commonly attached diagonally at the corners of doors, windows, or other areas prone to cracking. It may also be used to span pipe chases or to reinforce other stress points, such as the corners of openings in the stucco membrane within the lath system. Striplath is an excellent mechanical break for painted steel when applying fireproofing.

For spray-fireproofing systems, strip lath provides pre-cut widths which are easy to install and meet requirements for mechanical breaks on painted steel.

Product Data & Ordering Information:

Material: 1.75 lb (minimum) expanded lath
G-60 Hot-Dipped Galvanized Steel, per ASTM C847

Dimensions: 4" or 6" wide in 4' or 8' lengths

| Size | Pcs./Ctn. | Ft./Ctn. | Lbs./Pallet |
|---------|-----------|----------|-------------|
| 4" x 8' | 75 | 600 | 39 lbs. |
| 6" x 8' | 75 | 600 | 60 lbs. |

Code Approvals & Performance Standards

- [ASTM A641](#) Standard Specification for Zinc-Coated (Galvanized) Carbon Steel Wire
- [ASTM C847](#) Standard Specification for Metal Lath
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [Intertek CCRR-0204](#) Metal Lath - Code Compliance Research Report
- [SDS For ASTM A653 Steel Finishing Products](#) For Interior Finishing and Exterior Finishing

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather and surface contamination conforming to ASTM C1063.

Limitations:

Galvanized steel products should not be used with magnesium oxychloride cement stucco or Portland cement stucco containing calcium chloride additives.

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

