

Outlet-Patch

Electrical Outlet-Patch

Outlet-Patch is an electrical outlet-patch that will not fuzz-up during sanding.

- Pre-cut to fit standard receptacle boxes
- Repairs and reinforces mis-cut or damaged areas around receptacle box
- Very fast, extremely strong

Product Data & Ordering Information:

Product Code	Width	Type	Pcs/Case Pack	Cases/Pallet
OP-2PK	4-3/4" x 6-1/4"	2 Pack Card	50 cards of 2	24
OP-100	4-3/4" x 6-1/4"	20 Count Bag	5 bags of 20	24
OP-500	4-3/4" x 6-1/4"	20 Count Bag	25 bags of 20	24

Code Approvals & Performance Standards

- [ASTM C1047](#) Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- [SDS Strait-Flex - Joint Tape](#) For Joint Tape

Installation

- To apply, lightly sand area to be repaired.
- Apply drywall compound 1/8"-1/4" thick directly to back of patch.
- Place patch over center of repair and wipe down flat to wall using joint knife.
- Immediately skim-coat patch and let dry.
- Apply second coat, let dry, and sand. Compound that remains on backside of Outlet-Patch makes patch very rigid in the damaged area.

