

## Strait-Flex® OS-400

### Stick Corner Bead - Paper-Faced Composite

Designed for outside 90° corners where large voids and irregularities occur. OS-400 can also be used on double 5/8" drywall applications. The diamond-punched paper edging allows for easier feathering, faster drying, and the highest bonding strength. Also guarantees an even lay-down of the paper, providing maximum adhesion with no rippling or blistering. Apply with all-purpose joint-compound.

- Double 5/8" drywall applications and outside 90° corners where there are large drywall irregularities
- Clean installation
- Composite backing provides a tough, durable corner with no rust
- Nose resists dents and ensures perfect corners without paper fuzz-up during finishing and sanding

### Product Data & Ordering Information

Product Code	Width	Length	Wholesale Case Pcs/Case Pack	Wholesale Case Cases/Pallet
OS400-8	4"	8'	50pcs. (400 lf)	32
OS400-9	4"	9'	50pcs. (450 lf)	32
OS400-10	4"	10'	50pcs. (500 lf)	32
OS400-12	4"	12'	50pcs. (600 lf)	32

### Code Approvals & Performance Standards

- [ASTM C1047](#) Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- [SDS Strait-Flex - Stick Corner Trims](#) For Stick Corner Trims

### Installation

- Cut Strait-Flex OS-400 to measured length.
- For vertical corners, cut 1/4" short of floor.
- Apply all-purpose joint compound with Mud-Pro2 (compound applicator) to corner bead; or apply compound to outside corners with a 5" or 6" taping knife.
- Press corner bead into wet compound by hand or use Strait-Flex's OS-400 Rolling Tool for fastest results.
- Adjust if necessary to create a straight line.
- Wipe down edges and let dry.
- Apply final coat, let dry, and sand.
- Repairs Over Painted Surfaces: Strait-Flex recommends the use of Strait-Flex Super-Bond mixed with all-purpose joint compound to enhance bondability.

### Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from weather and moisture.

