

## Ultra-Patch

### Drywall Patch

Ultra-Patch easily installs using standard drywall compounds and will not fuzz-up during sanding. One Ultra-Patch repairs holes up to three inches in diameter.

- Quickly repairs damage to drywall
- The most economical and permanent way to repair drywall
- Outperforms metal patches

### Product Data & Ordering Information:

Product Code	Width	Type	Pcs/Case Pack	Cases/Pallet
ULTP-2PK	6" dia.	2 Pack Card	50 cards of 2	24
ULTP-100	6" dia.	10 Count Bag	10 bags of 10	

### ASTM & Code Standards:

- ASTM C1047 - Standard Specification for Accessories for Gypsum Wallboard
- SDS & Product Certification Information is available at [www.clarkdietrich.com/SupportDocs](http://www.clarkdietrich.com/SupportDocs)

### Installation

- To apply, lightly sand area to be repaired.
- Apply drywall compound 1/8"-1/4" thick directly to back of patch.
- Place patch over center of repair and wipe down flat to wall using joint knife.
- Immediately skim-coat patch and let dry.
- Apply second coat, let dry, and sand. Compound that remains on backside of Perma-Patch makes patch very rigid in the damaged area.

### Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from weather and moisture.

