

## Commercial Strapping (CS2.5-150-33)

**Multipurpose pre-punched commercial coil stock used for bracing, bridging or tension strapping**

Coil Strapping is made in a variety of widths, each with a unique layout of pre-punch holes for a variety of fastening options to meet different application requirements.

### Product Data & Ordering Information:

<b>Material:</b>	50 ksi
<b>Coating:</b>	G60
<b>Thickness:</b>	33mils (20ga) 0.0346" Design thickness 0.0329" Minimum thickness
<b>Width:</b>	2-1/2"
<b>Packaging:</b>	150 foot Boxed Coil
<b>Product Weight:</b>	42.5 lbs/coil

### ALLOWABLE TENSION LOAD FOR:

#### CS2.5-150-33 33mils (20ga) - 2-1/2" Wide Commercial Strapping

Stud / Joist / Framing Thickness	33mils (20ga)	43mils (18ga)	54mils (16ga)	68mils (14ga)	Allowable Strap Tension
#10 Fasteners per Each End of Strap	10	7	7	7	1650 lbs

### Code Approvals & Performance Standards


- **ASTM A653** Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- **ASTM A1003** Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for Cold-Formed Framing Members
- **SDS For ASTM A1003 Steel Framing Products** For Interior Framing, Exterior Framing and Clips/Accessories

### Alternative Products:

- Flat Strapping

**Sustainability Credits** For more details and LEED letters contact Technical Services at 888-437-3244 or visit [clarkdietrich.com/LEED](http://clarkdietrich.com/LEED).

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).



- Widths Available: 1", 1-1/2", 2", 2-1/2" & 3"
- Available in 20, 18, 16 & 14 gauge
- Pre-punched for fast and accurate fastener attachment

