

E-Corner Bead

Fully embedded corner bead

Provides reinforcement like welded-wire or woven wire laths.

Fully embedded corner bead installed underneath the stucco finish for reinforcement, like welded wire corner bead. Nose is buried, not exposed. Works with diamond mesh, welded-wire or woven wire laths.

Vinyl is impervious to corrosion when coated in veneer plaster, wet joint compounds, or when placed in contact with steel or aluminum frames and resists impacts, dents, and damage during construction. No priming is required to add paint to vinyl products due to its paint adhesion properties. Vinyl has low electrical and thermal conductivity and is considered an excellent insulator, as well as being self-extinguishing and offering better resistance to burning than many other common building materials. Additionally, vinyl has a lower cost than equivalent products manufactured from zinc or aluminum, for use when the highest levels of corrosion resistance are required.

Product Data & Ordering Information:

Product code	Dimensions	Pcs./Box
E-Corner	2-1/2" x 2-1/2" flanges	50
	Angle of flanges is 80 Degrees, with flexibility	


ASTM & Code Standards:

- Material: ASTM D1784 and D4216 cell Class 13244C
- Installation: ASTM C1063 (Stucco), C1780-17 Standard Practice for Installation Methods for Adhered Veneer Stone
- SDS & Product Certification Information is available at www.clarkdietrich.com/SupportDocs


Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

09.22.00 (Supports for Plaster)



Corner Bead



Project Information

Name:
Address:

Contractor Information

Name:
Contact:
Phone:
Fax:

Architect Information

Name:
Contact:
Phone:
Fax: