

## 3/4" Splayed Inside Corner Cove

### Bullnose Corner Beads

3/4" radius, splayed inside corner cove that is designed to complement ClarkDietrich vinyl 3/4" bullnose splayed corner bead. Adjustable from 120° to 140° for off-angle inside corner conditions.

### Product Data & Ordering Information:

Product code	Radius	Flange	Length	Pcs/Box
ICC75 SP-8	3/4"	7/8"	8'	35
ICC75 SP-10	3/4"	7/8"	10'	35

### Code Approvals & Performance Standards

- [ASTM C840](#) Standard Specification for Application and Finishing of Gypsum Board
- [ASTM C1047](#) Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D3678](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior - Profile Extrusions
- [SDS Vinyl Corp](#) PVC Compounds

### Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

