

Mid Wall Weep Screed with Weep Holes/Tape

Designed to relieve stress and assist in controlling cracks

The mid-wall screeds have a built-in control joint to accommodate expansion/contraction of the separate substrates.

The screeds also provide casing termination with removable tape for a clean finish.

Product Data & Ordering Information:

Product code	Ground	Flange	Length	Pcs./Box
1578-50WX	7/8" x 1/2"	3-1/2"	10'	15
1578-58WX	7/8" x 5/8"	3-1/2"	10'	15

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1780](#) Standard Practice for Installation Methods for Cement-based Adhered Masonry Veneer
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D256](#) Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics
- [ASTM D638](#) Standard Test Method for Tensile Properties of Plastics
- [ASTM D648](#) Standard Test Method for Deflection Temperature of Plastics Under Flexural Load in the Edgewise Position
- [ASTM D696](#) Standard Test Method for Coefficient of Linear Thermal Expansion of Plastics Between - 30°C and 30°C with a Vitreous Silica Dilatometer
- [ASTM D790](#) Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

