

Inside Corner Control Joint

Used to straighten an inside corner for a neat, straight edge

Control Joints help with the embedment of the lath and flange while assisting with tying requirements of discontinuous lath to the joint.

Product Data & Ordering Information:

| Product code | Ground | Flange | Length | Pcs./Box |
|--------------|--------|--------|--------|----------|
| 3150IC | 1/2" | 3" | 10' | 30 |
| 3158IC | 5/8" | 3" | 10' | 26 |
| 3175IC | 3/4" | 3" | 10' | 26 |
| 3178IC | 7/8" | 3" | 10' | 16 |
| 31100IC | 1" | 3" | 10' | 16 |

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C841](#) Standard Specification for Installation of Interior Lathing and Furring
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1780](#) Standard Practice for Installation Methods for Cement-based Adhered Masonry Veneer
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

