

Expansion Joints (Slip Joint) 1/2" Reveal

Designed to relieve stress in wall and ceiling areas

Used where excessive horizontal and vertical movements might occur. Includes an additional design feature of a 1/2" reveal.

Product Data & Ordering Information:

| Product code | Ground | Pcs./Box |
|--------------|--------|----------|
| 4038-50 | 3/8" | 25 |
| 4050-50 | 1/2" | 25 |
| 4058-50 | 5/8" | 25 |
| 4075-50 | 3/4" | 25 |
| 4078-50 | 7/8" | 20 |
| 40100-50 | 1" | 20 |

Notes: 1/2" reveal (adj. 1/4" to 5/8") 4" to 4-3/8" overall width, perforated flanges.

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

