Wide Expansion Joints (Slip Joint) The technical content of this literature is effective 09/06/23 and supersedes all previous information.

Product Submittal Sheet

Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

09.22.00 (Supports for Plaster)

Wide Expansion Joints (Slip Joint) 1-1/2" Reveal

Designed to relieve stress in wall and ceiling areas

Used where excessive horizontal and vertical movements might occur. Includes an additional design feature of a 1-1/2" reveal.

Product Data & Ordering Information:

Product code	Ground	Pcs./Box
5038-150	3/8"	12
5050-150	1/2"	12
5058-150	5/8"	12
5075-150	3/4"	12
5078-150	7/8"	10
50100-150	1"	10

Notes:1-1/2" reveal (adj. 1-1/4" to 1-5/8"), 7" to 7-3/8" overall width, perforated flanges. Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.


Code Approvals & Performance Standards

- ASTM C1063 Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- ASTM C1861 Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- ASTM D1784 Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- ASTM D4216 Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- SDS Vinyl Corp PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.







Stucco

