

## Wide Expansion Joints (Slip Joint) 1/2" Reveal

**Designed to relieve stress in wall and ceiling areas**

Used where excessive horizontal and vertical movements might occur. Includes an additional design feature of a 1/2" reveal.

### Product Data & Ordering Information:

Product code	Ground	Pcs./Box
5038-50	3/8"	18
5050-50	1/2"	18
5058-50	5/8"	18
5075-50	3/4"	18
5078-50	7/8"	15
50100-50	1"	15

Notes: 1/2" reveal (adj. 1/4" to 5/8"), 6" to 6-3/8" overall width, perforated flanges.

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

### Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

### Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

