

Drip Casing - 3/8" Drip Leg

Drip leg moves moisture away from openings and foundation walls

Designed to be used as base support starter strips and perimeter casing beads for Exterior Insulation Finish Systems (EIFS). Caulk all intersections, butt joints, ends, and corners at the time of installation.

Product Data & Ordering Information:

Product Code	Insulation Thickness (C)	Back Flange (B)	Drip Leg (A)	PCS/Box
DCB50-38	1/2"	2"	3/8"	50
DCB58-38	5/8"	2"	3/8"	50
DCB75-38	3/4"	2"	3/8"	50
DCB78-38	7/8"	2"	3/8"	50
DCB100-38	1"	2"	3/8"	50
DCB150-38	1-1/2"	2"	3/8"	50
DCB200-38	2"	2"	3/8"	50
DCB300-38	3"	2"	3/8"	30
DCB400-38	4"	2"	3/8"	30

Contact your ClarkDietrich Sales Representative for profile and market availability

Notes: If weep holes are required, add W to the product code, example: DCBW75-25.

If arched profile is required, refer to [Archmaker Drip Flashing](#)

If 3" or 3-1/2" back flange is required, refer to [Drip Flashing](#).

Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1780](#) Standard Practice for Installation Methods for Cement-based Adhered Masonry Veneer
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [ASTM E2110](#) Standard Terminology for Exterior Insulation and Finish Systems (EIFS)
- [ASTM E2511](#) Standard Guide for Detailing of EIFS-Clad Barrier and Drainage Wall Assemblies
- [SDS Vinyl Corp](#) PVC Compounds

