

E-Flange™ Bandmaker™ Casing Bead

PVC Casing Bead with Embeddable Flange Design

E-Flange Bandmaker™ Casing Bead is designed with a reinforcing rib to assist in keying heavy material fills when "bands" are used in architectural designs.

E-Flange allows for 80% more stucco mix to flow through the flange, providing a more thorough and consistent embedment. The unique E-Flange shape also allows for quick and easy tying of lath and other accessories.

Vinyl is impervious to corrosion when coated in veneer plaster, wet joint compounds, or when placed in contact with steel or aluminum frames and resists dents, damage, and impacts during construction. No priming is required to add paint to vinyl products due to its paint adhesion properties. Vinyl has low electrical and thermal conductivity and is considered an excellent insulator, as well as being self-extinguishing and offering better resistance to burning than many other common building materials. Additionally, vinyl has a lower cost than equivalent products manufactured from zinc or aluminum, for use when the highest levels of corrosion resistance are required.

Product Data & Ordering Information:

Product code	Ground (A)	Flange (B)	Length	Pcs./Box
66100TEF	1"	1-3/4"	10'	75
66125EF	1-1/4"	1-3/4"	10'	50
66150EF	1-1/2"	1-3/4"	10'	50
66175EF	1-3/4"	1-3/4"	10'	40
66200EF	2"	1-3/4"	10'	40

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C926](#) Standard Specification for Application of Portland Cement - Based Plaster
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1330](#) Standard Specification for Cylindrical Sealant Backing for Use with Cold Liquid-Applied Sealants
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [ASTM E331](#) Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

