

"F" Series Control Joint and Vent

Designed to work on narrow overhangs

Used where vents are needed to go against fascia or walls. Vent clips are provided to connect soffit vents and a perforated flange aids in embedment.

Product Data & Ordering Information:

Product code	Ground	Reveal Width	Overall Width	Vent Area per LF	Pcs./Box
F1538R-300V	3/8"	3"	5"	15 sq. in.	15
F1550R-300V	1/2"	3"	5"	15 sq. in.	15
F1558R-300V	5/8"	3"	5"	15 sq. in.	12
F1575R-300V	3/4"	3"	5"	15 sq. in.	12
F1578R-300V	7/8"	3"	5"	15 sq. in.	10
F15100R-300V	1"	3"	5"	15 sq. in.	10

Note: F15 Series can be ordered with the 300VFZ clip for installation.



Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C926](#) Standard Specification for Application of Portland Cement - Based Plaster
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.



- Available in 2", 3" and 4" reveal widths