

## "F" Series Control Joint and Vent

### Designed to work on narrow overhangs

Used where vents are needed to go against fascia or walls. Vent clips are provided to connect soffit vents and a perforated flange aids in embedment.

### Product Data & Ordering Information:

Product code	Ground	Reveal Width	Overall Width	Vent Area per LF	Pcs./Box
F1538R-400V	3/8"	4"	6"	16 sq. in.	12
F1550R-400V	1/2"	4"	6"	16 sq. in.	12
F1558R-400V	5/8"	4"	6"	16 sq. in.	10
F1575R-400V	3/4"	4"	6"	16 sq. in.	8
F1578R-400V	7/8"	4"	6"	16 sq. in.	8
F15100R-400V	1"	4"	6"	16 sq. in.	8

Note: F15 Series can be ordered with the 300VFZ clip for installation.



Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

### Code Approvals & Performance Standards

- [ASTM C926](#) Standard Specification for Application of Portland Cement - Based Plaster
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

### Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.



- Available in 2", 3" and 4" reveal widths