

## DEFS "F" Control Joint with Removable Tape

### Designed to relieve stress caused by expansion and contraction

Control joint used for DEFS applications to relieve stress caused by expansion and contraction and control cracking in large areas of walls and ceilings at the juncture of dissimilar materials. The removable tape creates a mask over the expansion slot during installation for a clean finish. Large perforations allow the base coat mixture to easily flow through and bond to the substrate. Recommended usage is for every 130-140 sq. ft. with no one side being longer than 15ft. Caulk all intersections, butt joints, ends, and corners at the time of installation.

### Product Data & Ordering Information:

Product Code	Finish Thickness	Board Thickness	Perforated Flanges	V Reveal	PCS/Box
FDCJ-50V	1/16"	1/2"	5/8"	3/16"	30
FDCJ-58V	1/16"	5/8"	5/8"	3/16"	30



### Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

### Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

