

Prefabricated Panel Edge

Designed for systems that are manufactured into panels for job installation

Creates a termination at a panel edge in Exterior Insulation Finish Systems (EIFS). The perforated flanges allow the base coat mixture to easily flow through and bond to the substrate. Includes the Keylock™ Splice for connecting multiple sections and to assist in their alignment. Caulk all intersections, butt joints, ends, and corners at the time of installation.

Product Data & Ordering Information:

Product Code	Finish	Insulation	Solid	Perforated	PCS/Box
	Thickness	Thickness (A)	Flange (B)	Flange (C)	
PRE100-16	1/16"	1"	1"	1-1/8"	60
PRE150-16	1/16"	1-1/2"	1"	1-1/8"	40
PRE200-16	1/16"	2"	1"	1-1/8"	25

U.S. Patent Number 5,970,671 and 6,134,847

Code Approvals & Performance Standards

- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [ASTM E2110](#) Standard Terminology for Exterior Insulation and Finish Systems (EIFS)
- [ASTM E2273](#) Standard Test Method for Determining the Drainage Efficiency of Exterior Insulation and Finish Systems (EIFS) Clad Wall Assemblies
- [ASTM E2486](#) Standard Test Method for Impact Resistance of Class PB and PI Exterior Insulation and Finish Systems (EIFS)
- [ASTM E2511](#) Standard Guide for Detailing of EIFS-Clad Barrier and Drainage Wall Assemblies
- [ASTM E2568](#) Standard Specification for PB Exterior Insulation and Finish Systems
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

