

Casing Bead / Plaster Stop

Used to neatly terminate stucco and plaster

Terminates stucco and plaster against windows, doors and other dissimilar materials.

Product Data & Ordering Information:

Product code	Ground (A)	Flange (B)	Pcs./Box
6625	1/4"	1-3/4"	100
6638	3/8"	1-3/4"	100
6650	1/2"	1-3/4"	100
6658	5/8"	1-3/4"	100
6675	3/4"	1-3/4"	75
6678	7/8"	1-3/4"	75
66100	1"	1-3/4"	75

Note: If weep holes are required, add W to the product code, example 6625W.

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1780](#) Standard Practice for Installation Methods for Cement-based Adhered Masonry Veneer
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

