

1-3/4" Weep Screeds (Unperforated Flange)

Designed to direct moisture from the stucco and to act as a stop

Install on frame construction where stucco and foundation walls meet.

Product Data & Ordering Information:

Product code	Ground	Flange	Overall Height	Length	Pcs./Box
WS38-250U	3/8"	1-3/4"	2-1/2"	10'	70
WS50-250U	1/2"	1-3/4"	2-1/2"	10'	70
WS58-250U	5/8"	1-3/4"	2-1/2"	10'	70
WS75-250U	3/4"	1-3/4"	2-1/2"	10'	70
WS78-250U	7/8"	1-3/4"	2-1/2"	10'	60

Note: Also available with a perforated back flange. To order, remove U from the product code, example: WS50-250.

Colors available: Standard color White or Tan, Brown, Gray and Black. Call for pricing.

Code Approvals & Performance Standards

- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1780](#) Standard Practice for Installation Methods for Cement-based Adhered Masonry Veneer
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

