

Nail Stop Plates

CDNSP1, CDNSP2

Designed to prevent nails from piercing and damaging mechanical, electrical and plumbing pipes and lines. To protect supply lines, the nail stopper is installed over each point where utilities pass through framing members.

Product Data & Ordering Information:

Material	Structural Grade 50 Type H (ST50H), 50ksi (340 MPa)
Coating	G90 (Z275) hot-dipped galvanized coating
Thickness	16ga (54mil), 0.0566" Design thickness, 0.0538" Minimum thickness
Dimensions	CDNSP1 = 1-1/2" x 3" CDNSP2 = 1-1/2" x 6"
Packaging	100 pcs/ctn
Product weight	CDNSP1 = 0.07 lb/ea CDNSP2 = 0.14 lb/ea

Product code	Size
CDNSP1	1-1/2" x 3"
CDNSP2	1-1/2" x 6"

Code Approvals & Performance Standards

- [ASTM A653](#) Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- [ASTM A1003](#) Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for Cold-Formed Framing Members
- [SDS For ASTM A1003 Steel Framing Products](#) For Interior Framing, Exterior Framing and Clips/Accessories

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

