

Rolled Straps

CDRS150, CDRS200, CDRS250

Manufactured to resist tension load when attached to solid sawn or structural composite lumber metal plate connected trusses, framing members and wall members. ClarkDietrich Rolled Strapping (CDRS) are 1-1/4" wide with holes punched at 1-1/4" on center, in a staggered pattern. Strapping is manufactured in continuous rolls of 250 feet for 20 gauge, 200 feet for 18 gauge and 150 feet for 16 gauge.

Product Data & Ordering Information:

CDRS150

| | |
|-----------------------|---|
| Material | Structural Grade 50 Type H (ST50H), 50ksi (340 MPa) |
| Coating | G90 (Z275) hot-dipped galvanized coating (G185 available) |
| Thickness | 16ga (54mil), 0.0566" Design thickness, 0.0538" Minimum thickness |
| Dimensions | 1-1/4" x 150' |
| Packaging | 1 roll/ctn |
| Product weight | 25 lbs/ea |



CDRS200

| | |
|-----------------------|---|
| Material | Structural Grade 50 Type H (ST50H), 50ksi (340 MPa) |
| Coating | G90 (Z275) hot-dipped galvanized coating |
| Thickness | 18ga (43mil), 0.0451" Design thickness, 0.0428" Minimum thickness |
| Dimensions | 1-1/4" x 200' |
| Packaging | 1 roll/ctn |
| Product weight | 41 lbs/ea |



CDRS250

| | |
|-----------------------|---|
| Material | Structural Grade 50 Type H (ST50H), 50ksi (340 MPa) |
| Coating | G90 (Z275) hot-dipped galvanized coating |
| Thickness | 20ga (33mil), 0.0346" Design thickness, 0.0329" Minimum thickness |
| Dimensions | 1-1/4" x 250' |
| Packaging | 1 roll/ctn |
| Product weight | 39 lbs/ea |

Code Approvals & Performance Standards

- [ASTM A653](#) Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- [ASTM A1003](#) Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for Cold-Formed Framing Members
- [IAPMO ER-0176](#) Evaluation Report for Wood Framing Hangers and Anchors
- [SDS For ASTM A1003 Steel Framing Products](#) For Interior Framing, Exterior Framing and Clips/Accessories

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

| Product code | Strap Dimensions (in) | | Fasteners (Each End) | Southern Pine (0.55 Specific Gravity) | | | | Douglas Fir-Larch (0.50 Specific Gravity) | | | | Spruce-Pine-Fir (0.42 Specific Gravity) | | | |
|--------------|-----------------------|-------------|----------------------|---------------------------------------|------|------|------|---|------|------|------|---|------|------|------|
| | Width | Min. Length | | Allowable Upward Load (lbs) | | | | | | | | | | | |
| | | | | Load Duration Factor | | | | Load Duration Factor | | | | Load Duration Factor | | | |
| | | | | 1.00 | 1.15 | 1.25 | 1.60 | 1.00 | 1.15 | 1.25 | 1.60 | 1.00 | 1.15 | 1.25 | 1.60 |
| CDRS150 | 1-1/4 | 6-1/4 | (2) 0.131" x 1.5" | 215 | 250 | 270 | 345 | 200 | 230 | 250 | 320 | 170 | 200 | 215 | 275 |
| | | | (2) 0.148" x 1.5" | 260 | 300 | 325 | 415 | 240 | 275 | 300 | 385 | 205 | 235 | 260 | 330 |
| | | | (2) 0.162" x 2.5" | 310 | 355 | 385 | 495 | 285 | 325 | 355 | 455 | 245 | 280 | 305 | 390 |
| | | 8-3/4 | (3) 0.131" x 1.5" | 325 | 375 | 405 | 520 | 300 | 345 | 375 | 480 | 260 | 295 | 320 | 415 |
| | | | (3) 0.148" x 1.5" | 390 | 450 | 485 | 625 | 360 | 415 | 450 | 575 | 310 | 355 | 385 | 495 |
| | | | (3) 0.162" x 2.5" | 460 | 530 | 575 | 740 | 425 | 490 | 535 | 680 | 365 | 420 | 460 | 585 |
| | | 11-1/4 | (4) 0.131" x 1.5" | 430 | 495 | 540 | 690 | 400 | 460 | 500 | 640 | 345 | 395 | 430 | 550 |
| | | | (4) 0.148" x 1.5" | 520 | 595 | 650 | 830 | 480 | 550 | 600 | 765 | 410 | 475 | 515 | 660 |
| | | | (4) 0.162" x 2.5" | 615 | 710 | 770 | 985 | 570 | 655 | 710 | 910 | 490 | 560 | 610 | 780 |
| | | 13-3/4 | (5) 0.131" x 1.5" | 540 | 620 | 675 | 865 | 500 | 575 | 625 | 800 | 430 | 495 | 535 | 690 |
| | | | (5) 0.148" x 1.5" | 650 | 745 | 810 | 1040 | 600 | 690 | 750 | 960 | 515 | 595 | 645 | 825 |
| | | | (5) 0.162" x 2.5" | 770 | 885 | 960 | 1230 | 710 | 815 | 890 | 1135 | 610 | 700 | 765 | 975 |
| | | 16-1/4 | (6) 0.131" x 1.5" | 650 | 745 | 810 | 1040 | 600 | 690 | 750 | 960 | 515 | 595 | 645 | 825 |
| | | | (6) 0.148" x 1.5" | 780 | 895 | 975 | 1245 | 720 | 825 | 900 | 1150 | 620 | 710 | 775 | 990 |
| | | | (6) 0.162" x 2.5" | 925 | 1060 | 1155 | 1480 | 850 | 980 | 1065 | 1365 | 735 | 845 | 915 | 1175 |
| | | 18-3/4 | (7) 0.131" x 1.5" | 755 | 870 | 945 | 1210 | 700 | 805 | 875 | 1120 | 600 | 690 | 750 | 965 |
| | | | (7) 0.148" x 1.5" | 910 | 1045 | 1135 | 1455 | 840 | 965 | 1050 | 1340 | 720 | 830 | 900 | 1155 |
| | | | (7) 0.162" x 2.5" | 1080 | 1240 | 1345 | 1725 | 995 | 1145 | 1245 | 1590 | 855 | 985 | 1070 | 1370 |
| | | 21-1/4 | (8) 0.131" x 1.5" | 865 | 995 | 1080 | 1385 | 800 | 920 | 1000 | 1280 | 690 | 790 | 860 | 1100 |
| | | | (8) 0.148" x 1.5" | 1040 | 1195 | 1300 | 1660 | 960 | 1100 | 1200 | 1535 | 825 | 950 | 1030 | 1320 |
| | | | (8) 0.162" x 2.5" | 1230 | 1415 | 1540 | 1970 | 1135 | 1305 | 1420 | 1820 | 975 | 1125 | 1220 | 1565 |
| | | 23-3/4 | (9) 0.131" x 1.5" | 975 | 1120 | 1215 | 1555 | 900 | 1035 | 1125 | 1440 | 775 | 890 | 965 | 1240 |
| | | | (9) 0.148" x 1.5" | 1170 | 1345 | 1460 | 1870 | 1080 | 1240 | 1350 | 1725 | 925 | 1065 | 1160 | 1485 |
| | | | (9) 0.162" x 2.5" | 1385 | 1595 | 1730 | 1970 | 1280 | 1470 | 1600 | 1970 | 1100 | 1265 | 1375 | 1760 |
| | | 26-1/4 | (10) 0.131" x 1.5" | 1080 | 1245 | 1350 | 1730 | 1000 | 1150 | 1250 | 1595 | 860 | 990 | 1075 | 1375 |
| | | | (10) 0.148" x 1.5" | 1300 | 1490 | 1620 | 1970 | 1200 | 1375 | 1495 | 1915 | 1030 | 1185 | 1290 | 1650 |
| | | | (10) 0.162" x 2.5" | 1540 | 1770 | 1925 | 1970 | 1420 | 1635 | 1775 | 1970 | 1220 | 1405 | 1525 | 1955 |
| | | 28-3/4 | (11) 0.131" x 1.5" | 1190 | 1370 | 1485 | 1905 | 1100 | 1265 | 1375 | 1755 | 945 | 1085 | 1180 | 1515 |
| | | | (11) 0.148" x 1.5" | 1425 | 1640 | 1785 | 1970 | 1320 | 1515 | 1645 | 1970 | 1135 | 1305 | 1415 | 1815 |
| | | | (11) 0.162" x 2.5" | 1695 | 1950 | 1970 | 1970 | 1565 | 1795 | 1955 | 1970 | 1345 | 1545 | 1680 | 1960 |
| | | 31-1/4 | (12) 0.131" x 1.5" | 1295 | 1490 | 1620 | 1970 | 1200 | 1380 | 1500 | 1915 | 1030 | 1185 | 1290 | 1650 |
| | | | (12) 0.148" x 1.5" | 1555 | 1790 | 1945 | 1970 | 1435 | 1655 | 1795 | 1970 | 1235 | 1420 | 1545 | 1970 |
| | | | (12) 0.162" x 2.5" | 1850 | 1970 | 1970 | 1970 | 1705 | 1960 | 1970 | 1970 | 1465 | 1685 | 1830 | 1970 |
| | | 33-3/4 | (13) 0.131" x 1.5" | 1405 | 1615 | 1755 | 1970 | 1300 | 1495 | 1620 | 1970 | 1115 | 1285 | 1395 | 1790 |
| | | | (13) 0.148" x 1.5" | 1685 | 1940 | 1970 | 1970 | 1555 | 1790 | 1945 | 1970 | 1340 | 1540 | 1675 | 1970 |
| | | | (13) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1845 | 1970 | 1970 | 1970 | 1590 | 1825 | 1970 | 1970 |
| 36-1/4 | (14) 0.131" x 1.5" | 1515 | 1740 | 1890 | 1970 | 1400 | 1605 | 1745 | 1970 | 1205 | 1385 | 1505 | 1925 | | |
| | (14) 0.148" x 1.5" | 1815 | 1970 | 1970 | 1970 | 1675 | 1930 | 1970 | 1970 | 1445 | 1660 | 1805 | 1970 | | |
| | (14) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1710 | 1965 | 1970 | 1970 | | |
| 38-3/4 | (15) 0.131" x 1.5" | 1620 | 1865 | 1970 | 1970 | 1500 | 1720 | 1870 | 1970 | 1290 | 1485 | 1610 | 1970 | | |
| | (15) 0.148" x 1.5" | 1945 | 1970 | 1970 | 1970 | 1795 | 1970 | 1970 | 1970 | 1545 | 1780 | 1930 | 1970 | | |
| | (15) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1830 | 1970 | 1970 | 1970 | | |
| 41-1/4 | (16) 0.131" x 1.5" | 1730 | 1970 | 1970 | 1970 | 1595 | 1835 | 1970 | 1970 | 1375 | 1580 | 1720 | 1970 | | |
| | (16) 0.148" x 1.5" | 1970 | 1970 | 1970 | 1970 | 1915 | 1970 | 1970 | 1970 | 1650 | 1895 | 1970 | 1970 | | |
| | (16) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1955 | 1970 | 1970 | 1970 | | |
| 43-3/4 | (17) 0.131" x 1.5" | 1840 | 1970 | 1970 | 1970 | 1695 | 1950 | 1970 | 1970 | 1460 | 1680 | 1825 | 1970 | | |
| | (17) 0.148" x 1.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1750 | 1970 | 1970 | 1970 | | |
| | (17) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | | |
| 46-1/4 | (18) 0.131" x 1.5" | 1945 | 1970 | 1970 | 1970 | 1795 | 1970 | 1970 | 1970 | 1545 | 1780 | 1935 | 1970 | | |
| | (18) 0.148" x 1.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1855 | 1970 | 1970 | 1970 | | |
| | (18) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | | |
| 48-3/4 | (19) 0.131" x 1.5" | 1970 | 1970 | 1970 | 1970 | 1895 | 1970 | 1970 | 1970 | 1635 | 1880 | 1970 | 1970 | | |
| | (19) 0.148" x 1.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | | |
| | (19) 0.162" x 2.5" | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | 1970 | | |

- Notes:**
- 1 Product Steel Gauge: 16
 - 2 Overall Length of Rolled Strap (ft): 150
 - 3 Allowable load capacities are based on the tabulated species and load duration factor.

| Product code | Strap Dimensions (in) | | Fasteners (Each End) | Southern Pine (0.55 Specific Gravity) | | | | Douglas Fir-Larch (0.50 Specific Gravity) | | | | Spruce-Pine-Fir (0.42 Specific Gravity) | | | |
|--------------|-----------------------|-------------|----------------------|---------------------------------------|------|------|------|---|------|------|------|---|------|------|------|
| | Width | Min. Length | | Allowable Upward Load (lbs) | | | | | | | | | | | |
| | | | | Load Duration Factor | | | | Load Duration Factor | | | | Load Duration Factor | | | |
| | | | 1.00 | 1.15 | 1.25 | 1.60 | 1.00 | 1.15 | 1.25 | 1.60 | 1.00 | 1.15 | 1.25 | 1.60 | |
| CDRS200 | 1 1/4 | 6-1/4 | (2) 0.131" x 1.5" | 210 | 245 | 265 | 340 | 195 | 225 | 245 | 310 | 165 | 190 | 210 | 270 |
| | | | (2) 0.148" x 1.5" | 255 | 290 | 320 | 405 | 235 | 270 | 295 | 375 | 200 | 230 | 250 | 320 |
| | | 8-3/4 | (2) 0.162" x 2.5" | 305 | 350 | 380 | 485 | 280 | 320 | 350 | 445 | 240 | 275 | 300 | 385 |
| | | | (3) 0.131" x 1.5" | 315 | 365 | 395 | 505 | 290 | 335 | 365 | 465 | 250 | 290 | 315 | 400 |
| | | 11-1/4 | (3) 0.148" x 1.5" | 380 | 440 | 475 | 610 | 350 | 405 | 440 | 560 | 300 | 345 | 375 | 485 |
| | | | (3) 0.162" x 2.5" | 455 | 520 | 570 | 725 | 420 | 480 | 525 | 670 | 360 | 415 | 450 | 575 |
| | | 13-3/4 | (4) 0.131" x 1.5" | 420 | 485 | 525 | 675 | 390 | 450 | 485 | 625 | 335 | 385 | 420 | 535 |
| | | | (4) 0.148" x 1.5" | 510 | 585 | 635 | 815 | 470 | 540 | 585 | 750 | 405 | 465 | 505 | 645 |
| | | 16-1/4 | (4) 0.162" x 2.5" | 605 | 695 | 755 | 970 | 560 | 640 | 700 | 895 | 480 | 550 | 600 | 765 |
| | | | (5) 0.131" x 1.5" | 525 | 605 | 660 | 845 | 485 | 560 | 610 | 780 | 420 | 480 | 525 | 670 |
| | | 18-3/4 | (5) 0.148" x 1.5" | 635 | 730 | 795 | 1015 | 585 | 675 | 730 | 935 | 505 | 580 | 630 | 805 |
| | | | (5) 0.162" x 2.5" | 755 | 870 | 945 | 1210 | 700 | 805 | 870 | 1115 | 600 | 690 | 750 | 960 |
| | | 21-1/4 | (6) 0.131" x 1.5" | 635 | 730 | 790 | 1015 | 585 | 670 | 730 | 935 | 500 | 575 | 625 | 805 |
| | | | (6) 0.148" x 1.5" | 760 | 875 | 955 | 1220 | 705 | 810 | 880 | 1125 | 605 | 695 | 755 | 965 |
| | | 23-3/4 | (6) 0.162" x 2.5" | 910 | 1045 | 1135 | 1455 | 835 | 965 | 1045 | 1340 | 720 | 825 | 900 | 1150 |
| | | | (7) 0.131" x 1.5" | 740 | 850 | 925 | 1180 | 680 | 785 | 850 | 1090 | 585 | 675 | 730 | 935 |
| | | 26-1/4 | (7) 0.148" x 1.5" | 890 | 1025 | 1110 | 1425 | 820 | 945 | 1025 | 1310 | 705 | 810 | 880 | 1125 |
| | | | (7) 0.162" x 2.5" | 1060 | 1220 | 1325 | 1570 | 975 | 1125 | 1220 | 1565 | 840 | 965 | 1050 | 1340 |
| | | 28-3/4 | (8) 0.131" x 1.5" | 845 | 970 | 1055 | 1350 | 780 | 895 | 975 | 1245 | 670 | 770 | 835 | 1070 |
| | | | (8) 0.148" x 1.5" | 1015 | 1170 | 1270 | 1570 | 935 | 1080 | 1170 | 1500 | 805 | 925 | 1005 | 1290 |
| | | 31-1/4 | (8) 0.162" x 2.5" | 1210 | 1395 | 1515 | 1570 | 1115 | 1285 | 1395 | 1570 | 980 | 1100 | 1200 | 1535 |
| | | | (9) 0.131" x 1.5" | 950 | 1090 | 1185 | 1520 | 875 | 1005 | 1095 | 1400 | 755 | 865 | 940 | 1205 |
| | | 33-3/4 | (9) 0.148" x 1.5" | 1145 | 1315 | 1430 | 1570 | 1055 | 1215 | 1320 | 1570 | 905 | 1040 | 1130 | 1450 |
| | | | (9) 0.162" x 2.5" | 1365 | 1565 | 1570 | 1570 | 1255 | 1445 | 1570 | 1570 | 1080 | 1240 | 1350 | 1570 |
| | | 36-1/4 | (10) 0.131" x 1.5" | 1055 | 1215 | 1320 | 1570 | 975 | 1120 | 1215 | 1555 | 835 | 960 | 1045 | 1340 |
| | | | (10) 0.148" x 1.5" | 1270 | 1460 | 1570 | 1570 | 1170 | 1350 | 1465 | 1570 | 1005 | 1155 | 1260 | 1570 |
| | | 38-3/4 | (10) 0.162" x 2.5" | 1515 | 1570 | 1570 | 1570 | 1395 | 1570 | 1570 | 1570 | 1200 | 1380 | 1495 | 1570 |
| | | | (11) 0.131" x 1.5" | 1160 | 1335 | 1450 | 1570 | 1070 | 1230 | 1340 | 1570 | 920 | 1060 | 1150 | 1470 |
| | | 41-1/4 | (11) 0.148" x 1.5" | 1400 | 1570 | 1570 | 1570 | 1290 | 1480 | 1570 | 1570 | 1105 | 1275 | 1385 | 1570 |
| | | | (11) 0.162" x 2.5" | 1570 | 1570 | 1570 | 1570 | 1535 | 1570 | 1570 | 1570 | 1320 | 1515 | 1570 | 1570 |
| | | 43-3/4 | (12) 0.131" x 1.5" | 1265 | 1455 | 1570 | 1570 | 1170 | 1345 | 1460 | 1570 | 1005 | 1155 | 1255 | 1570 |
| | | | (12) 0.148" x 1.5" | 1525 | 1570 | 1570 | 1570 | 1405 | 1570 | 1570 | 1570 | 1210 | 1390 | 1510 | 1570 |
| | | 45-3/4 | (12) 0.162" x 2.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1440 | 1570 | 1570 | 1570 |
| | | | (13) 0.131" x 1.5" | 1370 | 1570 | 1570 | 1570 | 1265 | 1455 | 1570 | 1570 | 1085 | 1250 | 1360 | 1570 |
| | | 47-3/4 | (13) 0.148" x 1.5" | 1570 | 1570 | 1570 | 1570 | 1525 | 1570 | 1570 | 1570 | 1310 | 1505 | 1570 | 1570 |
| | | | (13) 0.162" x 2.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1555 | 1570 | 1570 | 1570 |
| | | 49-3/4 | (14) 0.131" x 1.5" | 1475 | 1570 | 1570 | 1570 | 1360 | 1565 | 1570 | 1570 | 1170 | 1345 | 1465 | 1570 |
| | | | (14) 0.148" x 1.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1410 | 1570 | 1570 | 1570 |
| | | 51-3/4 | (14) 0.162" x 2.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 |
| | | | (15) 0.131" x 1.5" | 1570 | 1570 | 1570 | 1570 | 1460 | 1570 | 1570 | 1570 | 1255 | 1440 | 1570 | 1570 |
| | | 53-3/4 | (15) 0.148" x 1.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1510 | 1570 | 1570 | 1570 |
| | | | (15) 0.162" x 2.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 |
| | | 55-3/4 | (16) 0.131" x 1.5" | 1570 | 1570 | 1570 | 1570 | 1555 | 1570 | 1570 | 1570 | 1340 | 1540 | 1570 | 1570 |
| | | | (16) 0.148" x 1.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 |
| | | 57-3/4 | (16) 0.162" x 2.5" | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 | 1570 |

- Notes:**
- 1 Product Steel Gauge: 18
 - 2 Overall Length of Rolled Strap (ft): 200
 - 3 Allowable load capacities are based on the tabulated species and load duration factor.

| Product code | Strap Dimensions (in) | | Fasteners (Each End) | Southern Pine (0.55 Specific Gravity) | | | | Douglas Fir-Larch (0.50 Specific Gravity) | | | | Spruce-Pine-Fir (0.42 Specific Gravity) | | | |
|--------------|-----------------------|-------------|----------------------|---------------------------------------|------|------|------|---|------|------|------|---|------|------|------|
| | | | | Allowable Upward Load (lbs) | | | | | | | | | | | |
| | Width | Min. Length | | Load Duration Factor | | | | Load Duration Factor | | | | Load Duration Factor | | | |
| | | | | 1.00 | 1.15 | 1.25 | 1.60 | 1.00 | 1.15 | 1.25 | 1.60 | 1.00 | 1.15 | 1.25 | 1.60 |
| CDRS250 | 1-1/4 | 6-1/4 | (2) 0.131" x 1.5" | 205 | 235 | 255 | 325 | 190 | 215 | 235 | 300 | 160 | 185 | 200 | 260 |
| | | | (2) 0.148" x 1.5" | 245 | 285 | 310 | 395 | 225 | 260 | 285 | 365 | 195 | 225 | 245 | 310 |
| | | | (2) 0.162" x 2.5" | 295 | 340 | 370 | 470 | 270 | 315 | 340 | 435 | 235 | 270 | 290 | 375 |
| | | 8-3/4 | (3) 0.131" x 1.5" | 305 | 350 | 380 | 490 | 280 | 325 | 350 | 450 | 240 | 280 | 300 | 385 |
| | | | (3) 0.148" x 1.5" | 370 | 425 | 460 | 590 | 340 | 390 | 425 | 545 | 295 | 355 | 365 | 470 |
| | | | (3) 0.162" x 2.5" | 440 | 510 | 555 | 710 | 410 | 470 | 510 | 655 | 350 | 400 | 435 | 560 |
| | | 11-1/4 | (4) 0.131" x 1.5" | 405 | 470 | 510 | 650 | 375 | 430 | 470 | 600 | 325 | 370 | 405 | 515 |
| | | | (4) 0.148" x 1.5" | 495 | 565 | 615 | 790 | 455 | 520 | 570 | 725 | 390 | 450 | 490 | 625 |
| | | | (4) 0.162" x 2.5" | 590 | 680 | 735 | 835 | 545 | 625 | 680 | 835 | 465 | 535 | 585 | 745 |
| | | 13-3/4 | (5) 0.131" x 1.5" | 510 | 585 | 635 | 815 | 470 | 540 | 585 | 750 | 405 | 465 | 505 | 645 |
| | | | (5) 0.148" x 1.5" | 615 | 710 | 770 | 835 | 570 | 655 | 710 | 835 | 490 | 560 | 610 | 780 |
| | | | (5) 0.162" x 2.5" | 735 | 835 | 835 | 835 | 680 | 780 | 835 | 835 | 585 | 670 | 730 | 835 |
| | | 16-1/4 | (6) 0.131" x 1.5" | 610 | 700 | 765 | 835 | 565 | 650 | 705 | 835 | 485 | 555 | 605 | 775 |
| | | | (6) 0.148" x 1.5" | 740 | 835 | 835 | 835 | 680 | 785 | 835 | 835 | 585 | 675 | 730 | 835 |
| | | | (6) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 815 | 835 | 835 | 835 | 700 | 805 | 835 | 835 |
| | | 18-3/4 | (7) 0.131" x 1.5" | 710 | 820 | 835 | 835 | 655 | 755 | 820 | 835 | 565 | 650 | 705 | 835 |
| | | | (7) 0.148" x 1.5" | 835 | 835 | 835 | 835 | 795 | 835 | 835 | 835 | 685 | 785 | 835 | 835 |
| | | | (7) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 815 | 835 | 835 | 835 |
| | | 21-1/4 | (8) 0.131" x 1.5" | 815 | 835 | 835 | 835 | 750 | 835 | 835 | 835 | 645 | 740 | 805 | 835 |
| | | | (8) 0.148" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 780 | 835 | 835 | 835 |
| | | | (8) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | 23-3/4 | (9) 0.131" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 725 | 835 | 835 | 835 |
| | | | (9) 0.148" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | | (9) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | 26-1/4 | (10) 0.131" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 805 | 835 | 835 | 835 |
| | | | (10) 0.148" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | | (10) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | 28-3/4 | (11) 0.131" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | | (11) 0.148" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| | | | (11) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 |
| 31-1/4 | (12) 0.131" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | | |
| | (12) 0.148" x 1.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | | |
| | (12) 0.162" x 2.5" | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | 835 | | |

Notes:

- 1 Product Steel Gauge: 20
- 2 Overall Length of Rolled Strap (ft): 250
- 3 Allowable load capacities are based on the tabulated species and load duration factor.