

BlazeFrame® (ODSL 2)

“ODSL 2” (Offset Slotted Leg)

Two offset slotted lower legs w/ fire stop on both sides

Composite Fire Stop/Framing with “offset step” accommodates fireproofing in head of wall and wall to wall (column) assemblies. Provides joint protection for up to 1” with UL 2079 Class II or III Movement Capabilities. Minimum CP60 coating. Two legs with slots spaced 1” o.c. for positive attachment of studs per listed assemblies in UL Fire Resistance Directory.

A 2mm thickness of cured intumescent material adhered to metal profiles provides air, smoke and sound seals. When exposed to heat above 375 degrees Fahrenheit, the intumescent material expands up to 35 times its size. This provides protection from heat and flame passage during a fire event.

Product Data & Ordering Information:

Material:

Yield Strength: Grade 33ksi for 33mils & 43mils, 50ksi for 54mils
Coating: CP60 (G90 available)

33mils: 20 Gauge, 0.0346” Design Thickness, 0.0329” Min. Thickness

43mils: 18 Gauge, 0.0451” Design Thickness, 0.0428” Min. Thickness

54mils: 16 Gauge, 0.0566” Design Thickness, 0.0538” Min. Thickness

Dimensions:

Inside width: Equal to the outside width of the stud

Widths (W): 3-5/8”, 4”, 6” and 8”

Track length: 10’-0”

Profile	Lower Leg Length (L)	Tape Width (I)	Slot Height (S)	Joint Protection
ODSL 2	3.00”	1.00”	1.50”	0.75”
ODSLW 2	3.00”	1.25”	1.50”	1.00”

ASTM & Code Standards:

- ASTM A1003, C645 & C955
- UL2079, E1966, E119
- SDS & Product Certification Information is available at www.clarkdietrich.com/SupportDocs.


Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).


LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich’s steel products are 100% recyclable and have a minimum recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

09.22.16 (Non-Structural Metal Framing)



Fire Stop Deflection Track

- **UL Classified and Listed Joint Systems**
- **Intumescent strip provides air, smoke and sound seals**
- **Patents: www.cd-patents.com**



** Other offset step depths available

CD-BlazeFrame-ODSL2 © 12/1/17 ClarkDietrich Building Systems

Project Information

Name:
Address:

Contractor Information

Name:
Contact:
Phone:
Fax:

Architect Information

Name:
Contact:
Phone:
Fax: