

## Spazzer® 9200 Spacing and Bridging Bar

### Spazzer 9200 (Interior) Spacing and Bridging Bar

The Spazzer 9200 Bar is a prenotched bridging and spacing bar that facilitates the rapid erection of interior, nonload-bearing, nonstructural studs into a rigid, accurately laid out gridwork that has excellent resistance to stud rotation and displacement.

Spazzer 9200 Bar is a 33mils (20ga) bar that is 50" long and prenotched to hold studs rigidly on 16" or 24" centers. The slots have been pre-engineered to hold studs in place by utilizing "shear" to bridge studs into a rigid gridwork.

### Product Data & Ordering Information:

<b>Material:</b>	Grade 33ksi min. (230MPa)
<b>Coating:</b>	G40 (G60 available)
<b>Thickness:</b>	33mils (20ga) STR, 0.0346" Design Thickness, 0.0329" Min. Thickness
<b>Dimensions:</b>	7/8" x 7/8" (22.2mm x 22.2mm)
<b>Stock Length:</b>	50" Long (1270mm)
<b>Packaging:</b>	25 pieces per carton / 1350 pieces per skid
<b>Product Weight:</b>	1.0 lb/piece

### Code Approvals & Performance Standards

- **AISI S220-15** North American Standard for CFS Framing - Nonstructural Members
  - (Compliant to ASTM C645 , but IBC replaced with AISI S220 in IBC 2015)
  - Section A4 Material - Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
  - Section C Installation - (Referencing ASTM C754)

### Alternative Products:

- **U-channel (CRC) with clip angles**
- Blocking and Strapping

**Sustainability Credits** For more details and LEED letters contact Technical Services at 888-437-3244 or visit [clarkdietrich.com/LEED](http://clarkdietrich.com/LEED).

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).



- Saves up to 40% in combined labor and material costs.
- Eliminates stud spacing layout.
- Eliminates clip angles and the labor required to install them.

