

09.22.16 (Non-Structural Metal Framing)



Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

# RC-1 ProPlus™ Resilient Channel (RCUR Heavy)

#### Heavy-duty single-leg resilient channel

Made of 22mil steel to provide a stiffer resilient channel (RC-1 ProPlus) is one of the most effective, lowcost methods of improving sound transmission loss through wood and steel frame partitions. It is used as a cross-furring member for resilient attachment of gypsum. Knurled face makes wallboard application

Resilient channel should be installed perpendicular to the framing members with the attachment flange of the RC-1 ProPlus installed along the bottom edge. Channel is pre-punched for screw attachments to wood or steel framing members. Nails are not recommended for attaching RC-1 ProPlus heavy-duty resilient channel to framing members.

### **Product Data & Ordering Information:**

Grade 33ksi min. yield strength
G40EQ (G40 or G60 available)
22mils
2" x 1/2" Deep
12'-0"
258 lbs/1000ft

## **Code Approvals & Performance Standards**


- AISI S220-20 North American Standard for Cold-Formed Steel Framing Nonstructural Members o (Compliant to ASTM C645, but IBC replaced with AISI S220 in IBC 2015)
- ASTM A1003 Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for **Cold-Formed Framing Members**
- ASTM C754 Standard Specification for Installation of Steel Framing Members to Receive Screw-Attached Gypsum Panel Products
- UL File Number R19331 Full list of ProSTUD, Spazzer, Resilient Channel, Sound Clip and Barrier Mesh UL design assemblies
- SDS For ASTM A1003 Steel Framing Products For Interior Framing, Exterior Framing and Clips/Accessories

#### **Related Accessories:**

RC-2 ProPlus<sup>™</sup> double-leg resilient channel

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).



- · Reduces sound transmissions
- Pre-punched for screws
- · Spacing of pre-punched openings vary per manufacturing location.



