

ClarkDietrich Metal Lath and Accessories Certification

April 5, 2011

ClarkDietrich Building Systems certifies that the metal lath produced by ClarkDietrich Building Systems is in accordance with ASTM C-847. ClarkDietrich metal plaster base (lath) and accessory products are manufactured in compliance with the American Society of Testing and Materials (ASTM), the 2006 International Code Council IBC & IRC, the Uniform Building Code (UBC), and the ML/SFA-920. ClarkDietrich certifies that all metal lath, trim and accessories meets or exceeds the following specifications and specified requirements as set forth.

1) Metal Lath:

2.5 & 3.4 Flat and Self-Furring Diamond Mesh Metal Lath

2.5 & 3.4 Flat and Self-Furring Paper-Back "APB" Diamond Mesh Metal Lath

3.4 High Rib Metal Lath

- | | |
|----------------|--|
| 1) ASTM C-847 | Standard Specification for Metal Lath |
| 2) ASTM C-841 | Standard Specification for Installation of Interior Lathing and Furring |
| 3) ASTM C-1063 | Standard Specification for Installation of Lathing and Furring for Portland Cement-Based Plaster |
| 4) CEGS 09100 | Furring (Metal) Lathing and Plastering |
| 5) CEGS 09205 | Metal Furring and Lathing |
| 6) QQ-L-101C | Federal Specifications for Metal Lath and other plaster bases |

2) Metal Lath Accessories:

A. Corner Beads, Casing Beads, Base Bead & Screeds and Expansion/Control Joints

- | | |
|-------------------------|--|
| 1) Interior ASTM C-841 | Standard Specifications for Installation of Interior Lathing and Furring. |
| 2) Exterior ASTM C-1063 | Standard Specification for Installation of Lathing and Furring for Portland Cement-Based Plaster |
| 3) CE 240.01 | Furring (Metal) Lathing and Plastering |

B. Cornerite

- | | |
|----------------|---|
| 1) ASTM C-841 | Standard Specification for Installation of Interior Lathing and Plastering. |
| 2) ASTM C-1063 | Standard Specification for Installation of Lathing and Furring for Portland Cement-Based Plaster. |

C. Cold Rolled Channels: (2)

- | | |
|---------------|---|
| 1) ASTM C-841 | Standard Specification for Installation of Interior Lathing and Furring |
| 2) CE 240.01 | Furring (Metal) Lathing and Plastering |

Notes:

- (1) All Metal Lath and Galvanized Accessories are fabricated from steel, G60 zinc coating by the hot dipped method, conforming to Specification ASTM-A 924 and ASTM A-653/A-653M.
- (2) All Weather Resistive Barrier Backing for Metal Lath conforms to Federal Specification UU-B-790a, Type 1, Grade D, Style 2 and is printed directly on the paper product.
- (3) All Zinc Accessories are manufactured using 99.97% pure zinc complying with ASTM B-69.
- (4) GREEN - The average recycle content for any given steel coil is 28.9% with a range of 25 - 35%.
Reference: 2006 statistics from the Steel Recycling Institute, www.recycle-steel.org

Definitions:

- | | |
|------|---|
| ASTM | = American Society for Testing and Materials |
| CEGS | = U.S. Corps of Engineers Guide Specification |
| CE | = U.S. Corps of Engineers |
| QQ | = U.S. Federal Specifications |